

Male Concealable Sizing Form

750A Fieldcrest Road, Eden, NC 27288 Nationwide: 866-517-1113 www.KDHdefensesystems.com

| Officers Name | | | | Date |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------|------------|--------------------------------------------------------|
| Department | | | | Badge No. |
| Telephone | Email | | | Sized By |
| Dealer-Distributor's Name (if Applicable) | - Linuii | P.O. No. | | Date Sized |
| IMPORTANT: DUTY PANTS & DUTY BELT MUST BE WO | | | DN TO ENGI | |
| INII OTTAKT. BOTT FAKTO & BOTT BEET MIGGT BE WORK TO ENGODIE AR ACCOMATE TO | | | | |
| WAIST/GIRTH MEASUREMENT: With officer wearing duty belt and standing with arms at side, measure around the officer's waist at the widest point. This is generally 2-inches above the duty belt or along the navel line. It is extremely important to have a relaxed stomach for the most accurate measurement. Record measurement. WAIST/GIRTH MEASUREMENT: inches CHEST MEASUREMENT: With officer standing in front of you with arms raised in a "T" position, wrap measuring tape around his chest at the widest point. Arms are then lowered to the sides in a relaxed position. Record measurement. CHEST MEASUREMENT: inches | | | | |
| FRONT SEATED MEASUREMENT: With officer seated in a relaxed position, begin your measurement 1-inch below the clavicle 'notch' to a point approximately 1-2 inches above the top of the duty belt. Keep the tape straight and ask the officer to stand while holding the top of the tape in place so you can see where the bottom of the panel will be while in a 'seated' and 'standing' position. The seated measurement is the most critical, as it ensures the delivered vest front panel bottom edge will not touch the duty | | | | |
| belt or its accessories while the office measurement. FRONT SEATED MEASURE | | inches | Vest Style | e: SLEEK SLITE VALOR UNIFORM SHIRT CARRIER |
| A BACK STANDING MEASUREMENT: Whi at their sides, locate the natural shoulder limiddle of the back. (Typically, the back serom that location, measure down to a point the duty belt equipment, ensuring that the the accessories on the officers's duty belt. BACK STANDING MEASURI | ne and select a parallel p houlder seam on a unifo nt approximately 1-2 included bottom edge will not co Record measurement. | oint in the orm shirt.) hes above | | Package: evel: ftin. lbs. Black Navy White Tan Brown |
| Special Instructions: | | | | |