

STRIKER ARDITI

RIFLE ENHANCED COMBAT HELMET LEVEL III+ STANDARD CUT



STANDARD CUT



FULLY LOADED
(MULTIPLE OPTIONS AVAILABLE)



RATCHET DIAL HARNESS

SPECIFICATIONS

- + **Protection:** Level III+ rifle rated ballistic helmet including frag protection
- + **Rifle Special Threat Tested:** According to proprietary test requirements as defined by U.S. DOD
- + **MIL-STD 662F:** This product has been independently tested by an NVLAP accredited NIJ approved laboratory against FRAG resistance as specified under MIL-STD 662F
- + **XTclave:** Made in XTclave™ Ultra High Pressure Consolidation. XTclave™ is a composite curing and consolidation technology that makes it possible to manufacture lighter, stronger and stiffer composite articles.
- + **Materials:** 100% UHMWPE DSM Dyneema
- + **Head Protection:** Front, back, crown, and side of the head
- + **Weight:** 11 kgsm areal density, 1.2kg total weight (raw shell weight only, based on size large)
- + **Thickness:** 11mm
- + **Adjustable Harness:** Multiple harness options available, comes standard with Striker Ratchet Dial Harness
- + **Padding:** D30 TRUST 7 Pad helmet system
- + **Sizing:** Circumference is measured around the head, similar to hat sizing. All sizes are measured in inches. If a measurement falls on a dividing line between sizes, select the larger of the two sizes to ensure maximum ballistic protection.
- + **Warranty:** 5 years on all ballistic material excluding exterior cover, 1 year on exterior cover material and workmanship

COLORS

BLACK

OD GREEN

COYOTE

SIZE & WEIGHT CHART

SIZE	LENGTH	WIDTH	CIRCUMFERENCE		WEIGHT		
S	6.6" to 7.6"	4.9" to 5.9"	19.1" to 22.2"	485 mm to 564 mm	1567 g	1.6 kg	3.5 lbs
M	7.0" to 7.9"	5.1" to 6.1"	20.1" to 23.2"	510 mm to 590 mm	1631 g	1.6 kg	3.6 lbs
L	7.3" to 8.3"	5.5" to 6.5"	21.0" to 24.1"	533 mm to 613 mm	1723 g	1.7 kg	3.8 lbs
XL	7.9" to 8.9"	5.9" to 6.9"	22.4" to 25.6"	569 mm to 649 mm	1809 g	1.8 kg	4 lbs

Please Note: The size chart is based on 1/2" (size 4), 3/4" (size 6), 1" (size 8) pad systems. Standard pads offered are 3/4" Weights listed above are for a finished product including helmet shell, interior pads, and suspension with harness.

RIFLE THREATS

PROJECTILE	GR	VEL FT/S	VEL M/S	[+/- FT/S]	[+/- M/S]
7.62 x 51mm FMJ, steel jacketed bullets (M80)	147	2894	882	(+/- 50 fps)	(+/- 50 fps)
7.62 x 39mm (M43 MSC PS)	123	2390	728	(+/- 30 fps)	(+/- 30 fps)
5.56 x 45mm M193 FMJ	55	3251	991	(+/- 30 fps)	(+/- 30 fps)

MIL-STD 662F FRAG THREATS

PROJECTILE	GR	VEL FT/S	VEL M/S	V50 FT/S	V50 M/S
US Mil-Std Frag 2 gr. RCC	2	4200	1280	5391	1643
US Mil-Std Frag 4 gr. RCC	4	3475	1059	5163	1574
US Mil-Std Frag 16 gr. RCC	16	2475	754	4074	1242
US Mil-Std Frag 64 gr. RCC	64	1750	533	2852	869
US Mil-Std Frag 17 gr. FSP	17	2200	671	4187	1276
US Mil-Std Frag 44gr. FSP	44	1750	533	1851	564

HIGHCOMARMOR.COM



XTCLAVE TECH



RIFLE RATED



MIL-STD 662F



MULTI HIT



LIGHTWEIGHT