

# RAZOR XT

# LEVEL IIIA

## TECHNICAL SPECIFICATIONS

<b>Model Designation</b>	RZR-XT-III A
<b>Certified to NIJ-0101.06 Threat Level</b>	III A
<b>Test ID #</b>	RZR-XT-III A
<b>NIJ Certified Sizes</b>	C1 - C5
<b>Gender</b>	Neutral
<b>Ballistic Material</b>	Twaron® Flex Woven Aramid & Dyneema® UHMWPE, FMT
<b>Pad Cover</b>	Seam-sealed, waterproof Ripstop Nylon

<b>Weight (Areal Density)</b>	0.84 lbs/ft <sup>2</sup>
<b>Thickness</b>	0.20 in
<b>V-50 - .357 SIG</b>	1,876 ft/s
<b>V-50 - .44 Mag.</b>	1,722 ft/s
<b>Certification BFS - .357 SIG</b>	26.9 mm
<b>Certification BFS - .44 Mag.</b>	35.2 mm
<b>Warranty</b>	5 Years

## SPECIAL THREATS\*

Weapon	Ammunition
BROWNING 12ga.	Federal Tru Ball LE127RS - 1 oz. Slug
FN HERSTAL 5.7x28	Hornady SS1995LF - 27 gr.
S&W M&P 9mm	Winchester +P+ T-Series (SXT) - 127gr.
FN HERSTAL 5.7x28	Hornady SS197SR V-Max - 40 gr.

\*Special threat testing conducted in the Armor Express' state-of-the-art Ballistic Research Laboratory using the NIJ-0101.06 shot pattern.

