

TECHNICAL SPECIFICATIONS 800 SERIES BALLISTIC INSERTS

4800LV

SPECIAL RIFLE THREATS • Stand Alone
Special Order Item



THICKNESS: 0.67 in (17 mm)

SHOOTER CUT - MULTI CURVE - TORSO PLATES

PART NUMBER	WIDTH x LENGTH	WEIGHT
4800LV-SH-MC-L	10.0 x 12.0 in (254 x 305 mm)	4.7 lb (2.1 kg)
4800LV-SH-MC-S	8.0 x 10.0 in (203 x 254 mm)	3.0 lb (1.4 kg)

SAPI CUT - MULTI CURVE - TORSO PLATES

PART NUMBER	WIDTH x LENGTH	WEIGHT
4800LV-SA-MC-XL	11.00 x 14.00 in (279 x 356 mm)	6.5 lb (3.0 kg)
4800LV-SA-MC-L	10.25 x 13.25 in (260 x 337 mm)	5.6 lb (2.6 kg)
4800LV-SA-MC-M	9.50 x 12.50 in (241 x 318 mm)	4.9 lb (2.2 kg)
4800LV-SA-MC-S	8.75 x 11.75 in (222 x 298 mm)	4.2 lb (1.9 kg)



Manufacturing Tolerances:

Thickness dimensions are ±1/8 in (± 3 mm). Width and length dimensions are +0.00 to -0.25 in (+0.00 to -6 mm). All weights are ± 5%.

THREAT PERFORMANCE MATRIX: 4800LV	LEAD CORE			MILD STEEL CORE			ENHANCED PERFORMANCE			ARMOR PIERCING CORE		
	5.56 x 45 mm - M193 Max Velocity 2950 ft/s (900 m/s)	7.62 x 39 mm - M67 Max Velocity 2390 ft/s (728 m/s)	7.62 x 51 mm - M80 * Max Velocity 2800 ft/s (853 m/s)	7.62 x 63 mm - JSR Max Velocity 2780 ft/s (847 m/s)	5.56 x 45 mm - M855/JS109 Max Velocity 2950 ft/s (900 m/s)	7.62 x 39 mm - M43 Max Velocity 2390 ft/s (728 m/s)	5.56 x 45 mm - M855-A1 Max Velocity 2950 ft/s (900 m/s)	7.62 x 51 mm - M80A1 Max Velocity 2950 ft/s (900 m/s)	7.62 x 39 mm - API Max Velocity 2390 ft/s (728 m/s)	7.62 x 51 mm - API Max Velocity 2850 ft/s (869 m/s)	7.62 x 63 mm - M67 Max Velocity 2830 ft/s (863 m/s)	7.62 x 63 mm - AP M2 ** Max Velocity 2900 ft/s (884 m/s)
4800LV-SH-MC-L	3	3	3	3	3	3	3	3	1	3	1	1
4800LV-SH-MC-S	3	3	3	3	3	3	3	3	1	3	1	1
4800LV-SA-MC-XL	3	3	3	3	3	3	3	3	1	3	1	1
4800LV-SA-MC-L	3	3	3	3	3	3	3	3	1	3	1	1
4800LV-SA-MC-M	3	3	3	3	3	3	3	3	1	3	1	1
4800LV-SA-MC-S	3	3	3	3	3	3	3	3	1	3	1	1

* NIJ Level III Certification Threat ** NIJ Level IV Certification Threat

Hesco Special Threat Testing

NIJ Certification of hard armor requires submission of 10" x 12" test plates which must demonstrate the ability to defeat specific rounds tested to a valid NIJ shot pattern, after exposure to a stringent conditioning protocol to simulate aging and wear. Level III requires six M80 rounds per plate. Level IV requires one AP M2 per plate.

For reduced thickness, the 4800LV does not have front face or back face foam layers and therefore **does not meet the drop test or backface signature deformation requirements of NIJ Standard-0101.06**. Otherwise, its ballistic performance is consistent with the 4800.

Hesco holds itself to a higher standard by publishing the minimum number of shots that each size plate can be expected to defeat under similar NIJ testing methods, as well as listing many additional threats not addressed under the NIJ Certification process. Those minimum numbers are shown here.

General Information

Advanced ceramic/Spectra® design. Water repellent polyurethane coated CORDURA® fabric finish. Made in the U.S.A.

WARNING: HANDLE WITH EXTRA CARE!
AVAILABLE TO QUALIFIED AGENCIES ONLY.

Export Control Advisory

Model 4800LV (USML Category X(d)(1)) is subject to the International Traffic in Arms Regulations (ITAR). It may not be sold or otherwise provided to any non-U.S. Person and/or exported or re-exported without a valid U.S. Department of State DDTC export license, or applicable ITAR license Exemption.

Hesco Armor, Inc.
2210 Port Industrial Road
Aberdeen WA 98520, United States
Telephone: +1 360 637 6867

Hesco Group
Unit 41, Knowsthorpe Way
Leeds LS9 0SW, United Kingdom
Telephone: +44 113 248 6633
Email: support@hesco.com

Disclaimer: The information contained in this document is intended solely to provide general guidance. The right is reserved to make changes to this document without notice at any time. Nothing in this document (i) constitutes an offer, representation, warranty, term or condition or (ii) is a substitute for the need to employ adequate independent technical expertise and judgment.

Patents and Trademarks: HESCO® products are subject to patents and/or patent applications in territories around the world. HESCO® is a registered trademark of Hesco Bastion Ltd and its affiliates ("Hesco") around the world. Other trademarks also apply. For full details, please go to: www.hesco.com/legal_notice

Quality Standards: Hesco operates a Quality Management System certified to ISO 9001:2015/BA 9000:2016. Approved Certificate Number: C2019-01385. AQAP 2110 Conformance, Approved Certificate Number: C2019-01645.

This material is subject to copyright protection. Copyright © 2020 Hesco. All rights reserved.